



## Software Patent Institute Database of Software Technologies

### Record Display

### Record 1

Serial number TDB0991.0103

| Field Name                  | Contents of Record 1   |
|-----------------------------|--|
| Size of Record              | 1762 total bytes in record, 1573 in TX field   |
| Title                       | Elimination of <b>Surface Debris</b> in Laser Ablation of Polymers.  |
| Publication Date            | September, 1991  |
| Copyright Notices           | <p>This record was retrieved 15:17:19 Sat, Jan 22, 19100 from the SPI Database of Software Technologies Copyright © 1995-1998 Software Patent Institute.</p> <p>Database entry Copyright © Software Patent Institute This article is © Copyright IBM Corp.</p>   |
| Text of Submission          | <p>1 p. Disclosed is a process for preventing soot and <b>debris</b> accumulation surrounding laser ablation sites on an organic polymer <b>surface</b> by performing the ablation in helium or hydrogen gases.</p> <p>Organic polymers, such as KAPTON*, undergo efficient photoablation when irradiated by ultraviolet laser pulses of sufficient intensity (such as those from an excimer laser). The ablation process, when performed in air, results in the formation of soot and <b>debris</b> that surround the ablation site. For many applications, a clean <b>surface</b> following laser processing is required. Performing the ablation in low-mass gases, such as helium or hydrogen, at pressures near 1 atmosphere leaves the <b>surface</b> significantly cleaner than what occurs in air.</p> <p>Instead of having to flow the gas over the <b>surface</b> during laser ablation (*), simply immersing the polymer sample in a static chamber containing the gas will provide a clean <b>surface</b>. Further, utilizing the gas at pressures near 1 atmosphere provides a noticeably cleaner <b>surface</b> than that resulting from ablation in vacuum or low pressures. A significant advantage of using a static gas fill for cleaning purposes is that the gas can be slowly recirculated and thus reused. Flowing gas over the polymer <b>surface</b> in air is effective, but leads to increased amounts of needed gas. Additionally, operating at helium or hydrogen pressures of 1 atmosphere eliminates the need for pumping equipment with its added expense. * Trademark of E. I. du Pont de Nemours &amp; Co.</p> <p>Reference (*) Lambda Physik Highlights, No. 24, pp. 5-6, August 1990.</p> |
| Reference (pointer to work) | IBM TDB n4b 09-91 p233 Order: 91A 62406  |

|  |                   |
|--|-------------------|
| <b>Submission Date</b>                   | April, 1993       |
| <b>Date Loaded into Database</b>         | February 14, 1997 |
| <b>Publisher</b>                         | IBM Corporation.  |
| <b>Journal</b>                           | IBM TDB           |
| <b>Corporate Source</b>                  | IBM               |
| <b>Country of Origin</b>                 | U.S.A.            |
| <b>Publication Language</b>              | English           |
| <b>Source Type (Journal, book, etc.)</b> | journal           |

[New Search](#)[Modify Search](#)[Search Results](#)[Help \(Manual pages\)](#)[Search the Manual](#)[SPI Home](#)[Comments](#)

*This page was last revised Jan 14, 2000 by wem, bill@spi.org.*